



GE's LED fixture portfolio that ships in 3 or 5 business days



QUICKSHIP Portfolio

Indoor


LTL Series

2x2, 2x4



BT/BR/BV/ET Series

2x2, 2x4, and EMBB
Surface mount kits (BT, BR, BV,
AB, AC, AD)



LVT Series

2x2, 2x4



Refit Door Kit

2x2, 2x4



RX Series

6" & 8" - 1000, 1500, 2000 lm



DI Series

4" and 6" Round Housing
Infusion™ Light Modules
Reflectors



WS Series

4' Wrap Fixture
Narrow and Wide Body



FM Series

Flush Mount Fixture



RFR/SFF Series

Surface Mount Downlight



LTC Series

600 lm Track Light



QUICKSHIP Portfolio

Architectural

LLW Series
Wall Washer



Outdoor

Evolve™ LED – E2SA
Security Light



Evolve™ LED – EANB
Area Site Light



Evolve™ LED – EFNB
Flood Light



Evolve™ LED – EG2R
Garage Light



Evolve™ LED – EWS3
Area Light
Scalable Wall pack



QUICKSHIP Portfolio

Industrial

Albeo™ LED – ABR1

High Bay Luminaire



Albeo™ LED – ABV2

High Bay Luminaire



Albeo™ LED – ALR1

4' and 8' Linear Fixture



Albeo™ LED – ALV1

4' and 8' Linear Fixture



Indoor Fixtures

Lumination™ LTL Series LED Luminaires



- Ideal for general indoor lighting in office, commercial, retail and education applications
- Fits perfectly into T-grid drop ceilings for easy high-tech retrofits
- Provides high uniformity across the lens
- Available in 2x2 and 2x4 models
- CCT: 3500K, 4000K, 5000K
- Typical CRI of 83+
- 2x2: 30-38W at 3300-4000 lumens
- 2x4: 36-47W at 4000-4800 lumens
- L70 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ LTL Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93038953	LTL22A020MM835VQLTWHT	2X2, 120-277V, 2000 lumen, 80 CRI, 3500K, 0-10V	1-40	5 days	41-200	2 weeks
93038954	LTL22A020MM840VQLTWHT	2X2, 120-277V, 2000 lumen, 80 CRI, 4000K, 0-10V	1-40	5 days	41-200	2 weeks
93038955	LTL24A030MM835VQLTWHT	2X2, 120-277V, 3000 lumen, 80 CRI, 3500K, 0-10V	1-40	5 days	41-200	2 weeks
93038956	LTL24A030MM840VQLTWHT	2X2, 120-277V, 3000 lumen, 80 CRI, 4000K, 0-10V	1-40	5 days	41-200	2 weeks
93038732	LTL22A033MM835VQLTWHT	2X2, 120-277V, 3300 lumen, 80 CRI, 3500K, 0-10V	1-40	3 days	81-200	2 weeks
93037164	LTL22A033MM840VQLTWHT	2X2, 120-277V, 3300 lumen, 80 CRI, 4000K, 0-10V	1-40	3 days	41-200	2 weeks
93039408	LTL22A033MM835VQLTWTEEL	2X2, 120-277V, 3300 lumen, 80 CRI, 3500K, 0-10V, Emergency Light	1-20	3 days	21-80	2 weeks
93039409	LTL22A033MM840VQLTWTEEL	2X2, 120-277V, 3300 lumen, 80 CRI, 4000K, 0-10V, Emergency Light	1-20	3 days	21-80	2 weeks
93039410	LTL24A048MM835VQLTWHT	2X4, 120-277V, 4800 lumen, 80 CRI, 3500K, 0-10V	1-80	3 days	81-200	2 weeks
93035531	LTL24A048MM840VQLTWHT	2X4, 120-277V, 4800 lumen, 80 CRI, 4000K, 0-10V	1-40	3 days	41-200	2 weeks
93039411	LTL24A048MM835VQLTWTEEL	2X4, 120-277V, 4800 lumen, 80 CRI, 3500K, 0-10V, Emergency Light	1-20	3 days	21-80	2 weeks
93039348	LTL24A048MM840VQLTWTEEL	2X4, 120-277V, 4800 lumen, 80 CRI, 4000K, 0-10V, Emergency Light	1-20	3 days	21-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ BT Series LED Luminaires



- Ideal for general indoor lighting in office, commercial, retail and education applications
- Fits perfectly into T-grid drop ceilings for easy high-tech retrofits
- Provides high uniformity across the lens
- Converts to surface mount with surface mount kit
- Available in 1x4, 2x2, and 2x4 models
- CCT: 3500K, 4000K
- Typical CRI of 80+
- 1x4: 42W at 4000-4200 lumens
- 2x2: 34W at 3300-3500 lumens
- 2x4: 43W at 4500-4700 lumens
- L70 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ BT Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
26798	BT220A2AVWHT	2X2, 120-277V, 3300 lumen, 80 CRI, 3500K, 0-10V	1-40	3 days	41-200	2 weeks
26844	BT240A2AVWHT	2X4, 120-277V, 4500 lumen, 80 CRI, 3500K, 0-10V	1-40	3 days	41-200	2 weeks

* Shipment time subject to inventory availability

Lumination™ BR Series LED Luminaires



- Ideal for general indoor lighting in office, commercial, retail and education applications
- Easy and quick install into T-bar ceiling grids
- Perfect for new construction, remodel or retrofit projects
- Drop down door with accessible components
- Converts to surface mount with surface mount kit
- Available in 1x4, 2x2 or 2x4 models
- CCT: 3500K, 4000K
- Typical CRI of 80+
- 1x4: 42W at 3800-4000 lumens
- 2x2: 37W at 3325-3500 lumens
- 2x4: 49W at 4750-5000 lumens
- L70 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ BR Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
94994	BR220A2AVWHT	2X2, 120-277V, 3325 lumen, 80 CRI, 3500K, 0-10V	1-40	5 days	41-200	2 weeks
95053	BR240A2AVWHT	2X4, 120-277V, 4750 lumen, 80 CRI, 3500K, 0-10V	1-40	5 days	41-200	2 weeks

* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ BV Architectural Series LED Luminaires



- Provides visual appeal ideal for office, retail, or any space that requires a three dimensional look
- Curving and delineated details add creative appeal
- High uniformity across the lens
- Converts to surface mount with surface mount kit
- Access to components from beneath the ceiling
- Available in 2x2 and 2x4 models
- CCT: 3500K, 4000K
- Typical CRI of 80+
- 2x2: 33W at 3200-3250 lumens
- 2x4: 48W at 5100-5200 lumens
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ BV Architectural Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
27075	BV220A3AVWHT	2X2, 120-277V, 3250 lumen, 80 CRI, 4000K, 0-10V	1-20	5 days	21-80	2 weeks
27084	BV220A2AVWHT	2X2, 120-277V, 3200 lumen, 80 CRI, 3500K, 0-10V	1-20	5 days	21-80	2 weeks
27482	BV240A3AVWHT	2X4, 120-277V, 5200 lumen, 80 CRI, 4000K, 0-10V	1-20	5 days	21-80	2 weeks
64096	BV240A2AVWHT	2X4, 120-277V, 5100 lumen, 80 CRI, 3500K, 0-10V	1-20	5 days	21-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ ET Series LED Luminaires



- Advanced edge lit LED optical system provides high uniformity, excellent efficiency, improved spacing criteria, and reduced glare
- Easily installs in the most commonly used T-bar ceiling grids
- Diffused lens gives an evenly illuminated appearance
- May come equipped with Intrinsix™ technology which provides uniform light distribution
- Available in 1x4, 2x2, and 2x4 models
- CCT: 3000K, 3500K, 4000K
- Typical CRI of 80+
- 1x4: 38W at 3800-4000 lumens
- 2x2: 42W at 3500-3900 lumens
- 2x4: 47-54W at 3800-4500 lumens
- L85 @ 50,000 hours
- 0-10V dimming, DALI

The descriptions above represent the entire portfolio of Lumination™ ET Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
69278	ET220A3AVWHT	2X2, 120-277V, 3900 lumen, 80 CRI, 4000K, 0-10V	1-40	5 days	41-200	2 weeks
69277	ET220A2AVWHT	2X2, 120-277V, 3700 lumen, 80 CRI, 3500K, 0-10V	1-20	5 days	21-200	2 weeks
67603	ET240A3AVWHT	2X4, 120-277V, 4000 lumen, 80 CRI, 4000K, 0-10V	1-20	5 days	21-80	2 weeks
67602	ET240A2AVWHT	2X4, 120-277V, 3800 lumen, 80 CRI, 3500K, 0-10V	1-20	5 days	21-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ LVT Series LED Luminaires



- Ideal for general indoor lighting in office, commercial, retail and education applications
- Fits perfectly into T-grid drop ceilings for easy high-tech retrofits
- Provides high uniformity across the lens
- Available in 1x4, 2x2, and 2x4 models
- CCT: 3500K, 4000K, 5000K
- Typical CRI of 80+
- 2x2: 19-47.5W at 2000-5000 lumens
- 2x4: 28-69.5W at 3000-7200 lumens
- L70 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ LVT Series LED Luminaires. For more in-depth information, please visit gelighting.com.





Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93041491	LVT22A033MM835VQLTWHT	2X2, 120-277V, 3300 lumen, 80 CRI, 3500K	1-80	5 days	81-200	2 weeks
93041945	LVT22A033MM840VQLTWHT	2X2, 120-277V, 3300 lumen, 80 CRI, 4000K	1-40	5 days	41-200	2 weeks
93043419	LVT22A033MM835VQLTWHTTEL	2X2, 120-277V, 3300 lumen, 80 CRI, 3500K, Emergency Light	1-20	5 days	21-80	2 weeks
93049018	LVT22A033MM840VQLTWHTTEL	2X2, 120-277V, 3300 lumen, 80 CRI, 4000K, Emergency Light	1-20	5 days	21-80	2 weeks
93046039	LVT24A048MM835VQLTWHT	2X4, 120-277V, 4800 lumen, 80 CRI, 3500K	1-80	5 days	81-200	2 weeks
93044222	LVT24A048MM840VQLTWHT	2X4, 120-277V, 4800 lumen, 80 CRI, 4000K	1-40	5 days	41-200	2 weeks
93050625	LVT24A048MM835VQLTWHTTEL	2X4, 120-277V, 4800 lumen, 80 CRI, 3500K, Emergency Light	1-20	5 days	21-80	2 weeks



* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ LED Refit Door Kit						
		<ul style="list-style-type: none"> • LED upgrade for Linear Fluorescent Fixtures • Simple and fast installation • Reduced glare • Provides high uniformity, great efficiency and reduced glare • Available in 2x2 and 2x4 models (1x4 custom) 		<ul style="list-style-type: none"> • CCT: 3500K, 4000K • Typical CRI of 80+ • 2x2: 21W at 1950-2000 lumens • 2x4: 36W at 3900-4100 lumens • L70 @ 50,000 hours • 0-10V Dimming 		
The descriptions above represent the entire portfolio of Lumination™ LED Refit Door Kits. For more in-depth information, please visit gelighting.com .						Small Lot
SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
208160	LED20/DK22/835/10/SO	2X2, 120-277V, 1950 lumen, 83 CRI, 3500K, 0-10V	1-20	3 days	21-80	2 weeks
208161	LED20/DK22/840/10/SO	2X2, 120-277V, 2000 lumen, 82 CRI, 4000K, 0-10V	1-40	3 days	41-80	2 weeks
208162	LED35/DK24/835/10/SO	2x4, 120-277V, 3900 lumen, 83 CRI, 3500K, 0-10V	1-20	3 days	21-80	2 weeks
208163	LED35/DK24/840/10/SO	2x4, 120-277V, 4100 lumen, 82 CRI, 4000K, 0-10V	1-80	3 days	81-200	2 weeks

* Shipment time subject to inventory availability


Lumination™ RX Series LED Downlights						
		<ul style="list-style-type: none"> • Ideal for office, retail, hospitals, schools, airports, government facilities and shopping malls • Visually pleasing and energy efficient • Great solution to replace 1 or 2-lamp CFL downlights • Extremely quick and easy installation into most 6-inch and 8-inch CFL rough-in frames 		<ul style="list-style-type: none"> • CCT: 3000K, 3500K, 4000K • Typical CRI of 82 • 6 inch: 14W at 1000 lumens • 8 inch: 14W at 1000 lumens; 19.5W at 1500 lumens; 25W at 2000 lumens • L70 @ 50,000 hours • Non-dimming 		
The descriptions above represent the entire portfolio of Lumination™ RX Series LED Downlights. For more in-depth information, please visit gelighting.com .						Small Lot
SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93034746	LRXR610840MD	6" Round, 120-277V, 1000 lumen, 82 CRI, 4000K, 0-10V	1-160	5 days	161-320	2 weeks
93034752	LRXR810840MD	8" Round, 120-277V, 1000 lumen, 82 CRI, 4000K, 0-10V	1-160	5 days	161-320	2 weeks
93034755	LRXR818840MD	8" Round, 120-277V, 1800 lumen, 82 CRI, 4000K, 0-10V	1-160	5 days	161-320	2 weeks
93034758	LRXR830840MD	8" Round, 120-277V, 3000 lumen, 82 CRI, 4000K, 0-10V	1-160	5 days	161-320	2 weeks
212702	RX610830MV	6" Round, 120-277V, 1000 lumen, 82 CRI, 3000K	1-160	5 days	161-320	2 weeks
212703	RX610835MV	6" Round, 120-277V, 1000 lumen, 82 CRI, 3500K	1-160	5 days	161-320	2 weeks
212705	RX810830MV	8" Round, 120-277V, 1000 lumen, 82 CRI, 3000K	1-160	5 days	161-320	2 weeks
212706	RX810835MV	8" Round, 120-277V, 1000 lumen, 82 CRI, 3500K	1-160	5 days	161-320	2 weeks
212707	RX810840MV	8" Round, 120-277V, 1000 lumen, 82 CRI, 4000K	1-160	3 days	161-320	2 weeks
212708	RX815830MV	8" Round, 120-277V, 1500 lumen, 82 CRI, 3000K	1-160	5 days	161-320	2 weeks
212709	RX815835MV	8" Round, 120-277V, 1500 lumen, 82 CRI, 3500K	1-160	5 days	161-320	2 weeks
212710	RX815840MV	8" Round, 120-277V, 1500 lumen, 82 CRI, 4000K	1-160	3 days	161-320	2 weeks
212711	RX820830MV	8" Round, 120-277V, 2000 lumen, 82 CRI, 3000K	1-160	5 days	161-320	2 weeks

* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ DI Series LED Downlights



- Ideal for retail, office and hospitality applications
- Changeable lighting module that can be scaled for any environment
- Available in four color temperatures and five lumen packages, all with 90+ CRI
- Reflector is available in narrow, medium and wide light distribution patterns
- Available in 4" and 6" round or square luminaires, wall washing is an option
- CCT: 2700K, 3000K, 3500K, 4000K
- Typical CRI of 90
- 4": 14W at 1000 lumens; 51W at 4000 lumens
- 6": 14W at 1000 lumens; 51W at 4000 lumens
- L85 @ 50,000 hours
- 0-10V dimming, Phase dimming to 10%

The descriptions above represent the entire portfolio of Lumination™ DI Series LED Downlights. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
83628	DI4SLL1V10HO	4" Square Housing-Only, Low-Lumen Platform, 120V, 0-10V	1-40	5 days	41-80	2 weeks
93020883	DI4SLL2V10HO	4" Square Housing-Only, Low-Lumen Platform, 277V, 0-10V	1-40	5 days	41-80	2 weeks
83624	DI4RLL1V10HO	4" Round Housing-Only, Low-Lumen Platform, 120V, 0-10V	1-40	5 days	41-80	2 weeks
83625	DI4RLL2V10HO	4" Round Housing-Only, Low-Lumen Platform, 277V, 0-10V	1-40	5 days	41-80	2 weeks
93020884	DI6SLL1V10HO	6" Square Housing-Only, Low-Lumen Platform, 120V, 0-10V	1-40	5 days	41-80	2 weeks
93019376	DI6SLL2V10HO	6" Square Housing-Only, Low-Lumen Platform, 277V, 0-10V	1-40	5 days	41-80	2 weeks
93020885	DI6SHL1V10HO	6" Square Housing-Only, High-Lumen Platform, 120V, 0-10V	1-40	5 days	41-80	2 weeks
93020886	DI6SHL2V10HO	6" Square Housing-Only, High-Lumen Platform, 277V, 0-10V	1-40	5 days	41-80	2 weeks
83630	DI6RLL1V10HO	6" Round Housing-Only, Low-Lumen Platform, 120V, 0-10V	1-40	5 days	41-80	2 weeks
83632	DI6RLL2V10HO	6" Round Housing-Only, Low-Lumen Platform, 277V, 0-10V	1-40	5 days	41-80	2 weeks
83633	DI6RHL1V10HO	6" Round Housing-Only, High-Lumen Platform, 120V, 0-10V	1-40	5 days	41-80	2 weeks
83638	DI6RHL2V10HO	6" Round Housing-Only, High-Lumen Platform, 277V, 0-10V	1-40	5 days	41-80	2 weeks
19394	DLM1000/935	1000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
19395	DLM1000/940/G2	1000 lumen, 90 CRI, 4000K	1-40	5 days	41-80	2 weeks
19485	DLM1500/935	1500 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
19492	DLM1500/940/G2	1500 lumen, 90 CRI, 4000K	1-40	5 days	41-80	2 weeks
19525	DLM2000/935	2000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
19526	DLM2000/940/G2	2000 lumen, 90 CRI, 4000K	1-40	5 days	41-80	2 weeks
19595	DLM3000/935	3000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
34178	DLM3000/940/G2	3000 lumen, 90 CRI, 4000K	1-40	5 days	41-80	2 weeks
34185	DLM4000/935	4000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
34186	DLM4000/940/G2	4000 lumen, 90 CRI, 4000K	1-40	5 days	41-80	2 weeks
93984	RDI4RWSDMR	4" Round Reflector, Wide Distribution, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93985	RDI4RWSDWT	4" Round Reflector, Wide Distribution, Semi-Diffuse, White Flange	1-80	5 days	81-200	2 weeks
93986	RDI4SWSDMR	4" Square Reflector, Wide Distribution, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93987	RDI4SWSDWT	4" Square Reflector, Wide Distribution, Semi-Diffuse, White Flange	1-80	5 days	81-200	2 weeks
93988	RDI6RNSDMR	6" Round Reflector, Narrow Distribution, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93989	RDI6RNSDWT	6" Round Reflector, Narrow Distribution, Semi-Diffuse, White Flange	1-80	5 days	81-200	2 weeks
93990	RDI6RWSDMR	6" Round Reflector, Wide Distribution, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93991	RDI6RWSDWT	6" Round Reflector, Wide Distribution, Semi-Diffuse, White Flange	1-80	5 days	81-200	2 weeks
93992	RDI6MSDMR	6" Square Reflector, Medium Distribution, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93993	RDI6MSDWT	6" Square Reflector, Medium Distribution, Semi-Diffuse, White Flange	1-80	5 days	81-200	2 weeks
93994	RDI6SWSDMR	6" Square Reflector, Wide Distribution, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93995	RDI6SWSDWT	6" Square Reflector, Wide Distribution, Semi-Diffuse, White Flange	1-80	5 days	81-200	2 weeks

* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ WS Series Surface Mount LED Luminaires



- Commercial ceiling fixture that provides high quality, excellent efficiency and reduced glare in cooler and wash down applications
- Upgrade to the Linear Fluorescent Fixture
- High uniformity
- Available in 2x2 and 2x4 models (1x4 custom)
- CCT:4000K
- Typical CRI of 80+
- L70 @ 50,000 hours
- Typical efficiency: 103-113 LPW

The descriptions above represent the entire portfolio of Lumination™ WS Series Surface Mount LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
26722	WS4N0A3SVWHT	Wrap 4'x7" (Narrow Body), 5600 lumen, 4000K, 0-10V	1-40	3 days	41-80	2 weeks
26787	WS4W0A3SVWHT	Wrap 4'x14" (Wide Body), 8000 lumen, 4000K, 0-10V	1-40	3 days	41-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ FM Series Surface Mount LED Luminaires



- Ideal for hospitality, office, and residential applications in retrofit and new construction
- Quick installation with included mounting brackets and hardware
- Light is distributed evenly without pixilation resulting in a soft glow around the fixture
- ENERGY STAR® certified
- CCT: 2700K
- Typical CRI of 80
- L70 @ 25,000 hours
- Typical efficiency: 65 LPW
- Non-dimming

The descriptions above represent the entire portfolio of Lumination™ FM Series Surface Mount LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
33741	LED15FMM9-W	9" Surface Light, 1000 lumen, 2700K	1-80	5 days	81-200	2 weeks
20433	LED15FMM12-W	12" Surface Light, 975 lumen, 2700K	1-80	5 days	81-200	2 weeks

* Shipment time subject to inventory availability

Lumination™ RFR/SFR Series Surface Mount LED Luminaires



- Easily installs into a junction box or downlight can
- Features a slim, modern design
- Provides uniform lit appearance
- Available in 4" round and 6" square
- CCT: 3000K, 3500K
- Typical CRI of 80+
- L70 @ 30,000 hours
- Typical efficiency: 65 LPW
- Dimming: 10-100 Triac (Phase) dimming

The descriptions above represent the entire portfolio of Lumination™ RFR/SFR Series Surface Mount LED Luminaires.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93029327	SFR6-15-108351VPHWT	6" Square Surface Mount Downlight	1-160	5 days	161-320	2 weeks
93029291	RFR5-11-078301VPHWT	4" Round Surface Mount Downlight	1-160	5 days	161-320	2 weeks
93034174	#4MTL	4" Surface Mount Kit	1-160	5 days	161-320	2 weeks

* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ LTC Series LED Track Light



- Stylish alternative to PAR lamp holder
- Affordable solution to bring a sleek, clean look to your space
- Flexibility to customize for your space with accessories, beam angles and colors

- CCT: 2700K, 3000K, 4000K
- Typical CRI of 90
- 9.2W at 600 lumens
- L70 @ 50,000 hours
- Dimming: Triac & ELV (Forward & Reverse Phase) dimming standard, down to 10%

The descriptions above represent the entire portfolio of Lumination™ LTC Series LED Track Lights. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93042342	LTCIDA106SP930PQJ1WHTE	LTC, 120V, 600 lumen, 90 CRI, 3000K, Spot, Juno Adapter, White	1-40	5 days	41-100	6 weeks
93042343	LTCIDA106SP930PQJ1BLCK	LTC, 120V, 600 lumen, 90 CRI, 3000K, Spot, Juno Adapter, Black	1-40	5 days	41-100	6 weeks
93042345	LTCIDA106SP930PQG1WHTE	LTC, 120V, 600 lumen, 90 CRI, 3000K, Spot, Global Adapter, White	1-40	5 days	41-100	6 weeks
93042346	LTCIDA106SP930PQG1BLCK	LTC, 120V, 600 lumen, 90 CRI, 3000K, Spot, Global Adapter, Black	1-40	5 days	41-100	6 weeks
93042415	LTCIDA106WF930PQJ1BLCK	LTC, 120V, 600 lumen, 90 CRI, 3000K, Wide Flood, Juno Adapter, Black	1-40	5 days	41-100	6 weeks

* Shipment time subject to inventory availability

Architectural Fixtures

Lumination™ Architectural LLW Series LED Wall Washers



- Precise use of light output / eliminates socket shadows that are common when using fluorescent fixtures
- Consistent color with 3-step MacAdam ellipse color binning
- Available in a variety of optics to architectural designs
- Field-adjustable mounting for precise fixture optimize angle
- Connect up to 300 fixtures in series
- Easy Installation

- Universal 120-277 input
- L85 at 50,000 hours
- 0-10V dimmable (as low as 3%)
- IP51, dry or damp location rated
- 5 year limited warranty
- No UV emissions

The descriptions above represent the entire portfolio of Lumination™ Architectural LLW Series LED Wall Washers. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
10739	LLWSOB004CV827VQTMWHT	Standard Output Cove, 120-277V, 400 lumen, 80 CRI, 2700K, 0-10V	1-200	5 days	201-500	2 weeks
10740	LLWSOB004CV830VQTMWHT	Standard Output Cove, 120-277V, 400 lumen, 80 CRI, 3000K, 0-10V	1-200	5 days	201-500	2 weeks
10741	LLWSOB004CV835VQTMWHT	Standard Output Cove, 120-277V, 400 lumen, 80 CRI, 3500K, 0-10V	1-200	5 days	201-500	2 weeks
10747	LLWSOB004CV840VQTMWHT	Standard Output Cove, 120-277V, 400 lumen, 80 CRI, 4000K, 0-10V	1-200	5 days	201-500	2 weeks
10750	LLWHOB007CV827VQTMWHT	High Output Cove, 120-277V, 700 lumen, 80 CRI, 2700K, 0-10V	1-200	5 days	201-500	2 weeks
10758	LLWHOB007CV835VQTMWHT	High Output Cove, 120-277V, 700 lumen, 80 CRI, 3500K, 0-10V	1-200	5 days	201-500	2 weeks
10763	LLWHOB007CV840VQTMWHT	High Output Cove, 120-277V, 700 lumen, 80 CRI, 4000K, 0-10V	1-200	5 days	201-500	2 weeks
10892	LLWHOB007GZ827VQTMWHT	High Output Grazer, 120-277V, 700 lumen, 80 CRI, 2700K, 0-10V	1-100	5 days	101-300	2 weeks
10895	LLWHOB007GZ830VQTMWHT	High Output Grazer, 120-277V, 700 lumen, 80 CRI, 3000K, 0-10V	1-100	5 days	101-300	2 weeks
10899	LLWHOB007GZ835VQTMWHT	High Output Grazer, 120-277V, 700 lumen, 80 CRI, 3500K, 0-10V	1-100	5 days	101-300	2 weeks
65467	LWW1-MT48/0	Mounting Track 48" (10)	1-300	5 days	301-600	2 weeks

* Shipment time subject to inventory availability



Outdoor Fixtures

Evolve™ LED Security Light – E2SA



- Ideal for outdoor work yards, roadside commercial establishments, suburban developments and rural areas
- Built to withstand harsh elements
- Die-cast aluminum housing
- Structured LED arrays for optimized type 3 and type 5 square distributions
- CCT: 4000K
- Typical CRI of 80
- L70 @ 100,000 hours
- 0-10V Dimming

The descriptions above represent the entire portfolio of Evolve™ LED Security Light – E2SA. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93023249	E2SA0A1B31402NN	Security, 120V-277V, 3,600 lumen, 4000K	1-10	5 days	11-99	2 weeks
215014	E2SA0B1B31402NN	Security, 120V-277V, 5,200 lumen, 4000K	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability

Evolve™ LED Area Light – EANB/EALS



- Ideal for site, area, and general lighting applications
- Provides uniformity, vertical light distribution, reduced on-site glare and effective security light levels
- Obtain efficient parking space with dimming and occupancy sensing features
- Multiple mounting options
- CCT: 4000K, 5000K
- Typical CRI of 70
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Evolve™ LED Area Light – EANB and EALS. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93041732	EANB0D37401CDKBZ	Area, 120V-277V, Asymmetric Wide Type III, 10,500 lumen, 4000K, Bronze	1-10	5 days	11-99	2 weeks
93054615	EANB0F37401CDKBZ	Area, 120V-277V, Asymmetric Wide Type III, 14,700 lumen, 4000K, Bronze	1-10	5 days	11-99	2 weeks
93032612	EALS010H4AF740NDD1DKBZ	Area, 120V-277V, Type IV, 20,000 lumen, 198W, 4000K, Universal Mounting Arm, Bronze	1-10	5 days	11-99	2 weeks
93032945	EALS010K4AF740NDD1DKBZ	Area, 120V-277V, Type IV, 27,900 lumen, 322W, 4000K, Universal Mounting Arm, Bronze	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability

Evolve™ LED Flood Light – EFNB/EFH1



- Ideal for flood lighting applications including: Billboard/bulletin, spot and flag poles, building façade and general parking
- Die-cast aluminum housing incorporating heat sink
- Reflective technology to optimize efficiency and minimize glare
- Multiple mounting options
- CTT: 4000K, 5000K
- Typical CRI of 70
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Evolve™ LED Flood Light – EFNB and EFH1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93054704	EFNB0F37401KDKBZ	Flood, 120V-277V, Asymmetric Wide Type III, 14,700 lumen, 4000K Bronze, Knuckle Mount	1-10	5 days	11-99	2 weeks
93037878	EFH1010AA66750ADT1DKBZ	Flood, 120V-277V, NEMA 6x6, 18,800 lumen, 150W, 5000K, Trunnion Mount, Bronze	1-10	5 days	11-99	2 weeks
93040050	EFH1010EE76750ADT1DKBZ	Flood, 120V-277V, NEMA 7x6, 38,100 lumen, 297W, 5000K, Trunnion Mount, Bronze	1-10	5 days	11-99	2 weeks
93035238	EFH1010EE66750ADT1DKBZ	Flood, 120V-277V, NEMA 6x6, 37,700 lumen, 297W, 5000K, Trunnion Mount, Bronze	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability



Outdoor Fixtures

Evolve™ LED Garage Light – EG2R



- Ideal for garage, warehouse, walkway and stairway lighting
- Die-cast aluminum housing incorporating heat sink
- Provides high uniformity and vertical light distribution
- Features programmable motion sensing, step dimming and daylight harvesting
- Standard color: White
- Available with seven different mounting options
- CCT: 4000K, 5000K
- Typical CRI of 70
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Evolve™ LED Garage Light – EG2R. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
210737	EG2R0A5PS5011WHTE	Garage, 120V-277V, 5,000 lumen, 5000K, White	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability

Evolve™ LED Area Light Scalable Wall Pack – EWS3



- Ideal for wall mounted, site, area, and general lighting applications
- Provides uniformity, vertical light distribution, reduced offsite visibility/on-site glare and effective security light levels
- Die-cast aluminum housing
- Operates well in cold temperatures
- CCT: 4000K, 5000K
- Typical CRI of 70
- L85 @ 50,000 hours

The descriptions above represent the entire portfolio of Evolve™ LED Area Light Scalable Wall Pack – EWS3. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93043900	EWS30A7D1401DKBZ	Wall Pack, 120V-277V, Asymmetric Forward, 2,900 lumen, 4000K, Bronze	1-10	5 days	11-99	2 weeks
93043863	EWS30C7D1501DKBZ	Wall Pack, 120V-277V, Asymmetric Forward, 5,000 lumen, 5000K, Bronze	1-10	5 days	11-99	2 weeks
93045237	EWS30E3D1501DKBZ	Wall Pack, 120V-277V, Asymmetric Forward, 8,600 lumen, 5000K, Bronze	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability



Industrial Fixtures

Albeo™ LED Luminaire – ABR1



- IP66 rated fixture for industrial environments with high ambient temperatures and wet applications
- Modular design: single and double fixture options
- Cable/chain, rod or pendant mount
- Daylight and motion controls
- CCT: 4000K, 5000K
- Typical CRI of 70
- Lumen output: 9,000-46,000 lm
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ABR1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93014044	ABR101H571NNSTANW	Highbay, 120-277V, 11,800 lumen, 5000K, 120°, 70 CRI, White	1-5	5 days	6 - 200	2 weeks
93014051	ABR101T571NNSTANW	Highbay, 120-277V, 8,800 lumen, 5000K, 120°, 70 CRI, White	1-5	5 days	6 - 200	2 weeks
213915	ABR102H571NNSTANW	Highbay, 120-277V, 23,000 lumen, 5000K, 120°, 70 CRI, White	1-5	5 days	6 - 200	2 weeks

* Shipment time subject to inventory availability

Albeo™ LED Luminaire – ABV2



- Ideal for warehouse, cold storage, industrial, gymnasium, sports arena, retail, and high-ceiling applications
- Modular design: 1 and 2 modules
- Combination of steel and aluminum housing
- Daylight and motion controls
- CCT: 4000K, 5000K
- Typical CRI of 70
- Lumen output: 9,000-24,000 lm
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ABV2. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93053082	ABV201T471NVSTKNW1PK	Highbay, 120-277V, 9,000 lumen, 4000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053084	ABV201T571NVSTKNW1PK	Highbay, 120-277V, 9,100 lumen, 5000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053097	ABV201V471NVSTKNW1PK	Highbay, 120-277V, 12,000 lumen, 4000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053098	ABV201V571NVSTKNW1PK	Highbay, 120-277V, 12,300 lumen, 5000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053100	ABV202T471NVSTKNW1PK	Highbay, 120-277V, 24,100 lumen, 4000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053102	ABV202T571NVSTKNW1PK	Highbay, 120-277V, 18,300 lumen, 5000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053103	ABV202V471NVSTKNW1PK	Highbay, 120-277V, 24,600 lumen, 4000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053104	ABV202V571NVSTKNW1PK	Highbay, 120-277V, 18,300 lumen, 5000K, 120°, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
93053896	ABV201T47DNVSTKNW1PK	Highbay, 120-277V, 9,000 lumen, 4000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks
93055029	ABV201T57DNVSTKNW1PK	Highbay, 120-277V, 9,100 lumen, 5000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks
93053897	ABV201V47DNVSTKNW1PK	Highbay, 120-277V, 12,000 lumen, 4000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks
93049864	ABV201V57DNVSTKNW1PK	Highbay, 120-277V, 12,300 lumen, 5000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks
93056566	ABV202T47DNVSTKNW1PK	Highbay, 120-277V, 24,100 lumen, 4000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks
93055286	ABV202T57DNVSTKNW1PK	Highbay, 120-277V, 18,300 lumen, 5000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks
93053900	ABV202V47DNVSTKNW1PK	Highbay, 120-277V, 24,600 lumen, 4000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks
93053901	ABV202V57DNVSTKNW1PK	Highbay, 120-277V, 18,300 lumen, 5000K, 120°, 70 CRI, White, Diffused Lens	1-10	5 days	11 - 800	2 weeks

* Shipment time subject to inventory availability



Industrial Fixtures

Albeo™ LED Luminaire – ALR1



- Ideal for low bay and task level applications in commercial, industrial, warehouse, office and education settings
- IP65 rated
- IP66 rated motion sensors
- Fiberglass housing with diffuser
- Chain or surface mount
- Available in 4' and 8' models
- CCT: 4000K, 5000K
- Typical CRI of 70
- Lumen output: 3,300-14,800 lm
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ALR1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time	Lot Size*	Lead Time*
216582	ALR101H4714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 lumen, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216579	ALR101H5714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 lumen, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216581	ALR101T4714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 lumen, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216578	ALR101T5714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 lumen, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216583	ALR101V4714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 14,800 lumen, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216580	ALR101V5714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 14,800 lumen, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks

* Shipment time subject to inventory availability

Albeo™ LED Luminaire – ALV1



- Ideal for low bay and task level applications in commercial, industrial, warehouse, office and education settings
- Recommended for low bay lighting at 20 ft. or lower
- Stamped metal housing
- Chain/cable or surface mount
- Available in 4' and 8' models
- CCT: 4000K, 5000K
- Typical CRI of 70
- Lumen output: 3,350-14,800
- L70 @ 100,000 hours

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ALV1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time	Lot Size*	Lead Time*
216576	ALV101H4714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 lumen, 4000K, 70 CRI, White	1-10	5 days	6 - 200	2-3 weeks
216573	ALV101H5714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 lumen, 5000K, 70 CRI, White	1-10	5 days	6 - 200	2-3 weeks
216575	ALV101T4714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 lumen, 4000K, 70 CRI, White	1-10	5 days	6 - 200	2-3 weeks
216572	ALV101T5714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 lumen, 5000K, 70 CRI, White	1-10	5 days	6 - 200	2-3 weeks
216577	ALV101V4714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 7,300 lumen, 4000K, 70 CRI, White	1-10	5 days	6 - 200	2-3 weeks
216574	ALV101V5714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 7,300 lumen, 5000K, 70 CRI, White	1-10	5 days	6 - 200	2-3 weeks
93044117	ALV10H47D4SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 lumen, 4000K, 70 CRI, White, Diffused lens	1-10	5 days	6 - 200	2-3 weeks
93044116	ALV10H57D4SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 lumen, 5000K, 70 CRI, White, Diffused lens	1-10	5 days	6 - 200	2-3 weeks
93044115	ALV10T47D4SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 lumen, 4000K, 70 CRI, White, Diffused lens	1-10	5 days	6 - 200	2-3 weeks
93044114	ALV10T57D4SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 lumen, 5000K, 70 CRI, White, Diffused lens	1-10	5 days	6 - 200	2-3 weeks
93044113	ALV10V47D4SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 7,300 lumen, 4000K, 70 CRI, White, Diffused lens	1-10	5 days	6 - 200	2-3 weeks

* Shipment time subject to inventory availability





www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company.
© 2016 GE.

MISC034 (Rev. 5/1/2017)