



INDOOR COMMERCIAL

Type: GECFL 334 MO (R-300) DL

Indoor decorative, recessed mounting Dark Light fixture suitable for GE make 3x34W High Lumen Biax Compact Fluorescent Lamp. The fixture is complete with all accessories including low loss, open construction copper ballast, power factor correction capacitor & is pre-wired upto the terminal block. The fixture is compatible to Armstrong/Particle board ceiling of 300x300mm module.

Applications:

Ideal in areas where low glare is desired such as:

- VDU stations.
- Electronic assembly.
- High precision areas like watch assembly.

Type	Type of Lamp	Rotor Holder	Power Factor	Mains Voltage (V)	Pack Qty. (Per Box)
GECFL 334 MO (R-300) DL	3x34 W	2 G 11	>0.9	240	2

Technical Specifications:

- Housing made of CRCA sheet steel 22/24 SWG, painted stove enamelled white.
- Low loss , open construction, vacuum impregnated ballast.
- Mirrors made of very high purity anodised aluminium sheet for best optical efficacy. V-shaped cross louvers for reduced brightness desired in low glare applications.
- A separate earthing terminal provided inside the luminaire for electrical safety.

Mounting Arrangement & cable entry:

The luminaire is provided with 19mm knockouts at the top for suspension from ceiling. The cable entry is through the knockouts.

