


# CSR Lamps

The GE CSR700/S/DE/72 lamp is a compact double ended metal halide lamp with a small arc gap of 4 mm providing greater optical control and luminance. This lamp is suitable for hot restrike with maximum seal temperatures up to 500° C. This lamp is used in the event lighting field.

## Product Description CSR700/S/DE/72

•Order Description	CSR700S/DE/72
•Product Code	41357
•Pack Quantity	10
•Rated Wattage	700W
•Rated Voltage	70± 10V
•Lamp Current(ECG/MCG)*	10A
•Ignition Voltage(cold/hot)	2.5/25MAX
•Lumens	59,000
•Lumens per watt	84
•Ra	>75
•Chromaticity coordinates	x 0.322 y 0.332
•Color temperature	7,200K
•Arc Length (C)	4mm
•Lamp length (A)	136 mm
•Light center length (B)	57.5 + 1
•Lamp diameter	MAX ? 20 mm
•Average rated life	750hr
•Base	Sfc 10-4 with notch



\*ECG = electronic control gear/ MCG = Magnetic control gear

## Lamp Operation

Burn Position	Any
Maximum Seal Temperature	500° C
Cooling	Forced Cooling/Fan

## Control Gear

The CSR700/S/DE/72 can be used on electronic or AC magnetic ballast/ igniters control gear.



GE imagination at work

GE and General Electric are both registered trademarks of the General Electric Company, USA. © General Electric Company (USA) 2006

GE Consumer & Industrial Specialty Lighting is constantly developing and improving its products. For this reason, all product descriptions in this brochure are intended as a general guide, and we may change specifications time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, GE Lighting cannot accept any liability arising from the reliance on such data to the extent permitted by law.

CSR700/S/DE/72 - Data sheet - April 2008